US009410698B2

(12) **United States Patent**
Mori

(10) **Patent No.: US 9,410,698 B2**
(45) **Date of Patent: Aug. 9, 2016**

(54) **TUBULAR BURNER**

(75) Inventor: **Keisuke Mori**, Nagoya (JP)

(73) Assignee: **RINNAI CORPORATION**, Aichi (JP)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 553 days.

(21) Appl. No.: **13/270,369**

(22) Filed: **Oct. 11, 2011**

(65) **Prior Publication Data**

US 2013/0089826 A1 Apr. 11, 2013

(51) **Int. Cl.**
F23D 14/08 (2006.01)
F23D 14/26 (2006.01)

(52) **U.S. Cl.**
CPC ***F23D 14/08*** (2013.01); ***F23D 14/26*** (2013.01); *F23D 14/085* (2013.01)

(58) **Field of Classification Search**
CPC F23D 14/08; F23D 14/26; F23D 14/085
USPC 431/354, 355
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

431,716	A *	7/1890	Canfield	431/354
790,714	A *	5/1905	Bray	239/553.5
1,163,650	A *	12/1915	Fogler	110/264
1,179,781	A *	4/1916	Varnum	431/330
1,354,295	A *	9/1920	Hamilton	239/432
1,908,135	A *	5/1933	Forster	239/432
2,365,945	A *	12/1944	Ferguson	239/425.5
2,901,032	A *	8/1959	Brola	431/264
2,929,442	A *	3/1960	Brola	431/262
3,074,469	A *	1/1963	Babbitt et al.	431/285
3,156,292	A *	11/1964	Ross	239/419.5
3,198,238	A *	8/1965	Hughes	431/349
3,288,198	A *	11/1966	Hein et al.	431/349
3,570,242	A *	3/1971	Leonardi	F23R 3/04 431/183
3,850,571	A *	11/1974	Zink et al.	431/349
4,846,716	A *	7/1989	Courrege	431/263
5,049,066	A *	9/1991	Kaiya et al.	431/352
5,186,620	A *	2/1993	Hollingshead	F23D 14/045 239/558
RE34,541	E *	2/1994	Kreiger	431/1
5,433,602	A *	7/1995	Sigler	431/286

(Continued)

FOREIGN PATENT DOCUMENTS

JP	57-127122 U	8/1982
JP	62-106212 A	5/1987

OTHER PUBLICATIONS

Office Action from Japanese Patent App. No. 2010-176153 (Feb. 18, 2014).

Primary Examiner — Avinash Savani
Assistant Examiner — Aaron Heyamoto
(74) *Attorney, Agent, or Firm* — Cermak Nakajima & McGowan LLP; Tomoko Nakajima

(57) **ABSTRACT**

A tubular burner includes a mixing tube and a flame hole member having a plurality of flame holes. The flame hole member is made of a sheet metal plate and has: a circular disk part having the plurality of flame holes formed therein; and a fitting tubular member which is elongated backward from a periphery of the circular disk part and is adapted to be fitted into an inner circumference at the front end region of the mixing tube. A clearance-generating section is formed at a front of the fitting tubular member so as to generate an annular clearance between the clearance-generating section and the inner circumference at the front end region of the mixing tube. A plurality of flame retention holes are formed in the clearance-generating section at a circumferential distance from one another.

5 Claims, 4 Drawing Sheets